

# **SAFETY DATA SHEET**

# **Section 1: GENERAL INFORMATION**

TRADE NAME (Common Name or Synonym)

**CHEMICAL NAME** 

PREPARED BY

NC-900

Soldering Flux

Metallic Resources

**USED IN INDUSTRIAL SOLDERING PROCESSES** 

ADDRESS (No., Street, City, State, Zip Code):

Metallic Resources, Inc., 2368 East Enterprise Parkway, Twinsburg, OH 44087

CONTACT PHONE NUMBER

Metallic Resources, Inc.: (330) 425-3155

Chemtrec: (800) 424-9300

or contact any emergency room within 15 minutes of your location.

# **Section 2: HAZARDS IDENTIFICATION**

**Signal Word: Danger** 

#### **Hazard statement(s)**

H225 Highly flammable liquid and vapor

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

#### **Precautionary statement(s)**

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking

P233 Keep container tightly closed

P240 Ground/Bond container and receiving equipment

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + 351 IF IN EYES: Rinse continuously with water for several minutes

**GHS Category** 

Isopropyl alcohol:

Flammable liquid- Category 2

Skin irritation- Category 3

Eye irritation - Category 2A

#### **POTENTIAL HEALTH EFFECTS:**

**Eye Contact:** Vapors may be irritating, liquid may irritate or damage eye tissue. **Ingestion:** May result in gastric disturbances such as nausea and vomiting.





SDS-NC-900 Soldering Flux

# **Section 2: HAZARDS IDENTIFICATION (Continued)**

**Inhalation:** May cause irritation, headache or dizziness. Rosin has been known to cause occupational

asthma. Rosin may cause sensitization by inhalation.

**Skin Contact:** Prolonged contact may cause irritation, dermatitis or sensitization.

**Chronic:** Not established.

**NOTE:** Metallic Resources does not recommend, manufacture, market or endorse any of it's products for human

consumption.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS		
Material or Substance	C.A.S. #	Wt. %
2-Propanol	67-63-7	95-99%
Carboxylic Acid	68937-69-9	1-2%

#### **Section 4: FIRST AID MEASURES**

Eye Contact: Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Seek medical attention if

irritation persists.

**Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by

mouth to an unconscious person. Seek medical attention immediately.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

**Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If

irritation persists, obtain medical attention.

# **Section 5: FIRE FIGHTING MEASURES**

Flash Point: 54F (12C) Method: TCC Flammable

Auto-ignition Temperature: Not established

Flammable Limits: Not established

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions.

**Special Fire Fighting** Standard fire fighting equipment

**Procedures:** 

#### **Section 6: ACCIDENTAL RELEASE MEASURES**

**Spill or Leak Procedures:** DO NOT allow material to enter sewer system or waterway. Wear personal protective

equipment, such as gloves and depending on the quantity a respirator with organic cartridges may be required. Clean up by absorption. Eliminate sources of ignition. Keep unnecessary personnel away. Put clean-up materials in a properly labeled metal drum. Dispose of following all Federal, State and Local regulations. In the EU refer to the

Special Waste Regulations.

#### **Section 7: HANDLING AND STORAGE**

**Handling Precautions:** Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal

protective equipment. Ground containers when in use. Keep away from sources of heat.

**Storage Precautions:** Store product in tightly capped original containers in a cool, dry area, well ventilated

away from sources of ignition. Refer to product label for specific storage temperature

requirements. Rotate stock to ensure use before expiration date on the label.

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation is

recommended to keep exposure limits as low as possible. Keep exposure as low as

possible.

Personal protection:

**Eyes:** Chemical safety glasses/goggles. Face shield for splash hazards.

SDS-NC-900 Soldering Flux

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (Continued)

**Respirator:** A NIOSH approved or compliant marked air-purifying respirator with a fume/organic

chemical cartridge is recommended where airborne concentrations are expected to be

elevated.

**Skin:** Compatible chemical resistant gloves. Do not use latex gloves.

Other: Lab coat, sleeve protectors, eyewash fountain in work area. Avoid the use of contact

lenses in high fume areas.

Work/Hygienic Practices: Maintain good housekeeping. Clean up spills immediately.

Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

# **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Yellow liquid

Odor: Alcoholic

Boiling Point: Not available

Melting Point: Not applicable

**Specific Gravity:** 0.845 **pH:** Not applicable

Vapor Pressure: Not available Solubility in Water: Insoluble

Vapor Density: Not established

#### **Section 10: STABILITY AND REACTIVITY**

General: Stable.

**Conditions to Avoid:** Direct heat, open flames and storage in aluminum.

**Incompatible Materials:** phosphorus, halogens, anhydrides, monomers, aldehydes, trichlorides

**Hazardous Decomposition /** Carbon dioxide/carbon monoxide.

Combustion:

Hazardous Polymerization: Will not occur

# **Section 11: TOXICALOGICAL INFORMATION**

Carcinogenicity: NTP: No OSHA: No IARC: No

**LD50:** Not established. **LC50:** Not established.

# **Section 12: ECOLOGICAL INFORMATION**

No Data Available

#### **Section 13: DISPOSAL CONSIDERATION**

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local environmental regulations. In

Europe follow the Special Waste Regulations.

# **Section 14: TRANSPORT INFORMATION**

Transport in accordance with applicable regulations and requirements. UN1219, Isopropanol,3, PG II



# **Section 15: REGULATORY INFORMATION**

**UNITED STATES** 

**CERCLA:** Not subject to any special reporting under the requirements of CERCLA.

**TSCA Status:** All ingredients are listed or are exempt from listing (as polymers) under TSCA.

**CANADA** 

WHMIS (Canada): Class B Division 2, Class D Division 2B

California Proposition 65: When used for soldering and similar applications, the chemicals may be products which

are known to some states to cause birth defects or other reproductive harm.

**Reach Directive:** This product does not contain any Substances of Very High Concern (SVHC).

#### SDS-NC-900 Soldering Flux

# **Section 16: OTHER INFORMATION**

**ABBREVIATION TERMS:** 

ACGIH American Conference of Government Industrial Hygienists OSHA Occupational Safety and Health Act

CAS Chemical Abstracts Service PEL Permissible Exposure Limit
CEPA Canadian Environmental Protection Act REL Recommended Exposure Limit

IARC International Agency for Research on Cancer SARA Superfund Amendments & Reauthorization Act

NIOSH National Institute for Occupational Safety and Health TSCA Toxic Substances Control Act NTP National Toxicology Program N/A Not Applicable, Not Available

Issue Date: 5/1/15 Revised Date: 11/22/2022

Disclaimer Notice: The information contained herein in this Safety Data Sheet is believed to be accurate. However, it provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein. The customer/user of this product assumes all liability

and risk in the use of this product.