SAFETY DATA SHEET

Metallic Resou	Metallic Resources			
Section 1: 0	GENERAL INFORMATION			
	Common Name or Synonym)		CHEMICAL NAME	PREPARED BY
			Tin/Lead	Metallic Resources
	ad Solder Wire ISTRIAL SOLDERING PROCESSES		TIN/Lead	Metallic Resources
ADDRESS (No.	, Street, City, State, Zip Code):		011 (1007	
	ources, Inc., 2368 East Enterprise	Parkway, Twinsburg		
CONTACT			PHONE NUMBER	
	esources, Inc.:		(330) 425-3155	
Chemtrec			(800) 424-9300	
or contact	any emergency room within 15 minute	s of your location.		
Section 2: F	HAZARDS IDENTIFICATION	Ň		
Signal Word:				^
-	-			
Hazard staten				
	ful if swallowed			•/
•	cted of causing cancer (lead)			\sim
•	cted of damaging fertility or the un			^
	ause damage to organs through pr		exposure (lead)	
•	oxic to aquatic life with long lasting	g harmful effects		
	<u>v statement(s)</u>			
	container tightly closed			
	breathing dust/fume/gas/mist/vap			•
	t eat, drink or smoke when using th	his product		
	release to the environment			
	protective gloves/protective clothi		e protection	
	off contaminated clothing and wash			
P301 + P312	IF SWALLOWED: Call a POISON C		sician if you feel unwe	11
 P302 +P352 IF ON SKIN: Wash with plenty of soap and water P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comforta 				
P304 + 341	for breathing	alt, remove victim to m	esh ali and keep at re	est in a position confortable
P305 + 351	IF IN EYES: Rinse continuously wi	ith water for several m	ninutes (15 mins)	
P501	Dispose of contents by recycling			oved waste handler.
	. , , , ,	·		
Classification:				
Acute toxicity	, oral – Category 4			
Carcinogenicit				
•	toxicity- Category 2			
	organ toxicity – repeated exposur	• ,		
Acute aquatic	toxicity – Category 1 Chronic aqua	tic toxicity- Category 1	L	
POTENTIAL H	EALTH EFFECTS:			
Eve Contact:	Contact with nowered metal allo	w or fume from molte	n metal may cause irr	itation Sovere eve

Eye Contact: Contact with powered metal alloy or fume from molten metal may cause irritation. Severe eye damage may result from hot molten metal being splashed into the eyes. Wear safety glasses and face shield when working with molten metal.

SDS-TINLEAD WIRE I	ROSIN Tin,	Lead Soldering Wire
Section 2: H	HAZARDS IDENTIFICATION (Continued)	
Ingestion:	Ingestion of dust may cause headache, nausea, abdominal pain, fatigue and pain in the leg arms and joints. May be harmful.	ζS,
Inhalation:	Inhalation of fume or dust may cause local irritation to the respiratory system. Inhalation of fume or dust may cause headache, nausea, abdominal pain, fatigue and pain in the legs, a and joints. Inhalation can be harmful.	
Skin Contact:	Normal handling of solid metal should not cause any adverse health effects. Hot molten m cause burns to the skin. Wear protective equipment when handling molten metal. Protect grinding/cutting, may cause irritation.	•
Chronic:	<u>TIN:</u> Has been shown to increase incidence of sarcoma in animal tests. Chronic exposure result in "stannosis" a mild form of pneumoconiosis.	e may
	<u>LEAD:</u> Prolonged exposure to vapors or fumes at higher temperatures may cause respirate and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, ab muscle and joint pain and damage to the nervous system, blood system and kidneys.	
	Exposure to metal fumes may cause irritation to the respiratory system. Long term exposu inhalation to metal fumes may cause illness such as metal fume fever. Exposure to lead fume may cause harm. Sign of overexposure is anemia.	ire by
NOTE:	Metallic Resources does not recommend, manufacturer, market or endorse any of its products for human consumption.	

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS			
Material or Substance	C.A.S. #	Wt. %	
Tin	7440-31-5	59-64%	
Lead	7439-92-1	41-36%	
Rosin	65997-05-9	<3	

ye Contact:	Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
Ingestion:	If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
Skin Contact:	Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

Vapor Density:

Section 5: FIRE FIGHTI	NG MEASURES		
Flash Point: Not establish		t established.	
Auto-ignition Temperature:	Not established.		
Flammable Limits:	Limits not established. Massive metal is not flammable; however dust or powder m be a dust hazard.		
Extinguishing Media:	Use extinguishers appropri molten metal.	ate for the surrounding fire conditions. Never add water to	
Special Fire Fighting Firefighters must wear NIOSH approved self-contained breathing approved self-contained		SH approved self-contained breathing apparatus and full	
Procedures:	protective clothing.		
Section 6: ACCIDENTA	L RELEASE MEASURES	S	
Spill or Leak Procedures:	up and return to process. If DO NOT SWEEP, avoid gene barrels and return to proce	ol to allow metal to solidify. If a solid metal, wear gloves, pick f dust, wear recommended personal protective equipment. eration of dust. Ventilation required. Use a vacuum, place in ess if applicable. Otherwise, dispose of following all Federal, s. In the EU refer to the Special Waste Regulations. Metal has	
Section 7: HANDLING A	ND STORAGE		
Handling Precautions:	Only dry metals should be added to molten bath. If working with molten metals, or exposed to fume or dust, use appropriate personal protective equipment.		
Storage Precautions:		v area away from incompatible materials.	
Section 8: EXPOSURE C	CONTROLS/PERSONAL I	PROTECTION	
Engineering Controls:	Exhaust ventilation is required to control any air contaminants containing lead. Control concentration of all components so that their permissible exposure limits are not exceeded.		
Personal protection:			
Eyes:	Chemical safety glasses/go	ggles and face shield with molten metal.	
Respirator:	An authority approved or compliant marked air-purifying respirator with a fume/dust chemical cartridge is recommended under certain circumstances where airborne concentrations are expected to be elevated or if in powder form. Avoid inhalation of lead dust. Additional respiratory protection maybe required based on the work conditions.		
Skin:	Gloves-leather or impervious (vinyl) type. Heat resistant gloves if handling hot metal. Safety type boots. Personal protective equipment is recommended when working with molten metal to avoid burns.		
Other:	Lab coat, safety shower and eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.		
Work/Hygienic Practices:	Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area. Follow standard lead work practices as established under governmental regulations.		
Section 9: PHYSICAL A	ND CHEMICAL PROPER	RTIES	
Appearance:	Silver grey solid metal	Boiling Point: Not applicable.	
Odor:	Odorless	Melting Point: 361°F (182°C)	
Specific Gravity:	Alloy Dependent	pH: Not applicable	
Vapor Pressure:	Not applicable.	Solubility in Water: Insoluble	
Vanar Dansity	(air-1) Not applicable	Flach naint: Not applicable	

Flash point:

Not applicable

(air=1) Not applicable.

SDS-TINLEAD WIRE ROSIN

Section 10: STABILITY AND REACTIVITY

General:	Stable.
Conditions to Avoid:	Not established.
Incompatible Materials:	Avoid contact with mineral acids.
Hazardous Decomposition /	Harmful organic fumes and toxic oxide fumes may form at elevated
Combustion:	temperatures.
Hazardous Polymerization:	Will not occur.

Section 11: TOXICALOGICAL INFORMATION

Carcinogenicity:

National Toxicity Program (NTP): Yes- reasonably anticipated to be a human carcinogen Occupational Safety & Health Administration (OSHA): Yes- 1910.1025 U.N. International Agency for Research on Cancer (IARC): Yes Lead and Lead compounds are listed as possible carcinogens. 2B-Group 2B- possibly carcinogenic to humans. LD50: Not established LC50: Not established **Other:** Chronic Toxicity: Lead can cause potential harm to the developing fetus. Irritancy of Product: Not established Mutagenicity: Not established Sensitization to Product: Not established Teratogenicity: Not established **Reproductive Toxicity:** No specific data is available Synergistic Products: Not established

RTECS#: Lead – OF7525000 RTECS#: Tin – XP7320000 (Registry of Toxic Effects of Chemical Substances)

Lead

reproductive toxicity – rat –inhalation reproductive toxicity – rat – oral reproductive toxicity – mouse-oral

Teratogenicity Developmental toxicity – rat- inhalation Developmental toxicity- rat- oral Suspected human reproductive toxicant

GHS- Specific target organ toxicity- repeated exposure May cause damage to organs through prolonged or repeated exposure

Lead- OSHA Hazards- carcinogen/target organ effect/harmful by ingestion/teratogen.

Section 12: ECOLOGICAL INFORMATION

Product mixture not tested.

Lead – Toxicity to fish – mortality LOEC – rainbow trout – 1.19 mg/l – 96h. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Bioaccumulation – Oncorhynchus kisutch – 2 weeks Bioconcentration factor (BCF): 12. Fresh fish: 0.44 mg/l LC50 96h/ 1.32 mg/l LC50 96h/water Flea: 600 ug/l EC50 = 48h Avoid release to environment. Bioconcentration factor: BCF 12 Very toxic to aquatic life with long lasting effects.

Section 13: DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations. Avoid release to the environment.

Section 14: TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US DOT (United States Department of Transportation).

Metal solid form:

Not hazardous under shipping modes/ regulations.

UN - none

North American Emergency Guide Book - Not classified

Powder form: Only if it meets or exceeds the reportable quantity (RQ) of lead in a single package

RQ, UN 3077, Environmentally Hazardous Substance, Solid, 9, PG III (Lead)

Marine Pollutant: No

RQ (lead) = 10 lbs

Section 15: REGULATORY INFORMATION

UNITED STATES

HCS Classification: Toxic Material, Irritating material, carcinogen, target organ effects.

U.S. Federal Regulations: All ingredients comply with applicable rules or orders under US TSCA. All components are listed or exempted.

TSCA 6 proposed risk management: LEAD. TSCA 8(b) inventory: LEAD TSCA 12(b) annual export notification: LEAD

SARA 313	Substance Name
Form R - Reporting Requirements:	Lead
Supplier Notification:	Lead

California Prop. 65: This product contains a substance known to the State of California to cause cancer and birth defects or other reproductive harm.

WHMIS (Canada): Class D-2A: Material causing other toxic effects (very toxic). CEPA DSL: Tin, Lead.

Reach Directive: Contains Lead, a Substance of Very High Concern (SVHC).

Section 16: OTHER INFORMATION

ABBREVIATION TERMS:

- ACGIH American Conference of Government Industrial Hygienists
- CAS Chemical Abstracts Service
- CEPA Canadian Environmental Protection Act
- IARC International Agency for Research on Cancer
- NIOSH National Institute for Occupational Safety and Health
- NTP National Toxicology Program

- OSHA Occupational Safety and Health Act
- PEL Permissible Exposure Limit
- REL Recommended Exposure Limit
- SARA Superfund Amendments & Reauthorization Act
- TSCA Toxic Substances Control Act
- N/A Not Applicable, Not Available

 Issue Date:
 5/1/15

 Revised Date:
 1/22/2025

Disclaimer Notice: The information contained herein in this Safety Data Sheet is believed to be accurate. However, it provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein. The customer/user of this product assumes all liability and risk in the use of this product.